

# Steel Fixed Gantry Crane with Phenolic Casters 10 Ft. 6000 Lb. Capacity Blue

**MODEL FHS-6-10**

Overhead Lifting / Fixed Steel Gantry Cranes

## PRODUCT OVERVIEW

The fixed height steel gantry crane is designed for transporting and positioning materials along the beams length. The solid steel construction will provide years of service, while the painted blue finish will keep the models protected from surface ware. The rigging locks in 1 of 4 positions; you can set the wheels and push the gantry crane forward, back, left or right. The unit is an economical and efficient way to lift and raise products, diminishing the need of additional personnel. The fixed height design allows for constant use in a particular setting without the need to maneuver the overall height of the unit.

## KEY FEATURES

- Heavy-duty welded steel construction for long lasting use
- Each unit includes four swivel phenolic casters with four-way position locks for safe positioning
- The fixed height of the unit provides constant lifting stability
- All units comply with applicable OSHA 29 CFR 1910 179, ASME B30 17, ANSI Z535 4 specifications

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**775 lbs**

**ASSEMBLED SIZE**  
**65.5" W x 119.75" L x 129.3125" H**

**SHIP WEIGHT**  
**816 lbs**

**PACKAGE 1 SIZE**  
**65" W x 77" D x 19" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                                        |
|--------------------------------------|--------------------------------------------------------|
| Uniform Capacity (lb.)               | 6,000                                                  |
| Overall I-Beam Length (ft.)          | 10                                                     |
| Overall I-Beam Height (in.)          | 8-1/8                                                  |
| I-Beam Flange Width (in.)            | 4                                                      |
| Under I-Beam to Ground (in.)         | 121                                                    |
| Base Width (in.)                     | 65-1/2                                                 |
| Caster Quantity/Diameter/Width (in.) | (4) 8 x 3                                              |
| Caster Type                          | Swivel (4) Position Locking Casters w/ Roller bearings |
| Caster Material                      | Phenolic                                               |
| Usable Length (in.)                  | 89-3/4                                                 |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=519>