

# Steel Adjustable Double Mast Stacker 118 In. Raised Height Variable Speed 2200 Lb. Capacity Black

**MODEL S2-118-AA-VS**

Ergonomic Solutions / Variable Speed Drive Double Mast Fully Powered Stacker



## PRODUCT OVERVIEW

The double mast fully powered electric stacker transports loads throughout warehouse facilities quickly and with less effort. High torque drive and lift motor handles heavy duty jobs. Ergonomic handle features lift/lower controls, proprietary safety enhancing emergency reverse function, and horn. The unit includes an electromagnetic disc brake with automatic dead-man feature. Powered lifter has two 12V lead acid deep cycle batteries, integral battery charger, and a battery level gauge.

## KEY FEATURES

- Adjustable forks and legs
- Variable speed drive
- Automatic shut off is applied when handle disengaged
- Rolls smoothly on poly-on-steel steer and load wheels

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**1520 lbs**

**ASSEMBLED SIZE**  
**58" W x 76.625" L x 79" H**

**SHIP WEIGHT**  
**1550 lbs**

**PACKAGE 1 SIZE**  
**61" W x 71" D x 866" H**

**COLOR / FINISH**  
**Black**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                                                         |
|--------------------------------------|-------------------------------------------------------------------------|
| Uniform Capacity (Lbs.)              | 2,200                                                                   |
| Variable Speed Drive?                | Yes                                                                     |
| Fork Width (in.)                     | 8-5/16 to 26-3/4                                                        |
| Fork Length (in.)                    | 42                                                                      |
| Lowered Height (in.)                 | 2-9/16                                                                  |
| Raised Height (in.)                  | 118                                                                     |
| Battery                              | (2)12V                                                                  |
| Steer/Load Wheels Material           | Poly-On-Steel                                                           |
| Drive Motor                          | DC 24V                                                                  |
| Lift Motor                           | DC 24V                                                                  |
| Operation at Full Charge (hrs.)      | 3-4                                                                     |
| Operation at intermittent use (hrs.) | 8                                                                       |
| Style                                | Adjustable Forks / Adjustable Support Legs (works with pallets & skids) |
| Width Between Straddle Legs (in.)    | 40 to 50                                                                |
| Battery Depth                        | 13.5                                                                    |
| Battery Width                        | 6                                                                       |
| Battery Height                       | 10                                                                      |
| Battery Weight                       | 53                                                                      |
| Battery Freight Class                | 70                                                                      |
| Battery NMFC Number                  | 60680                                                                   |
| Battery NMFC Description             | UN2794 BATTERIES WET FILLED WITH ACID                                   |
| Battery Subclass                     | 1                                                                       |
| Lithium Battery Configuration        | C -- Contained In                                                       |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1807>