

# Steel Truck Dock Plate 36 In. x 72 In. x 8-11/16 In. 11,000 Lb. Capacity Yellow

**MODEL SEH-7236**

Loading Dock Equipment / Steel Truck Dockplates

## PRODUCT OVERVIEW

The steel truck dock plate is constructed of high strength INX-55 (55,000 psi) steel. Safety locking legs prevent slippage between truck and dock. Safety tread plate helps provide positive traction. Beveled edges for smooth entry and exit. Chain pickup comes standard. Designed with an 11 degrees bend located 9" from the beveled edge. The legs are 10" from the beveled edge. Manufactured in compliance with OSHA. When using three wheeled pallet trucks, select capacity +20% due to concentrated load center of board.

## KEY FEATURES

- Manufactured from high-strength steel tread plate for maximum durability
- Heavy-duty steel curbs are welded in place for maximum strength
- OSHA compliant locking legs secure dock plate when in use
- Beveled entry and exit edges provide a smooth transition

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**378 lbs**

ASSEMBLED SIZE  
**72" W x 36" L x 8.6875" H**

SHIP WEIGHT  
**385 lbs**

PACKAGE 1 SIZE  
**74" W x 37" D x 10" H**

COLOR / FINISH  
**Yellow**

FREIGHT TYPE  
**LTL Loose**

**AVAILABILITY** Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                       |        |
|---------------------------------------|--------|
| Uniform Capacity (lb.)                | 11,000 |
| Height Difference (in.)               | 5      |
| Steel Strength (psi)                  | 55,000 |
| Bend Degree                           | 11     |
| Bend Distance from Beveled Edge (in.) | 9      |
| Leg Distance from Beveled Edge (in.)  | 10     |
| Plate Thickness (in.)                 | 1/2    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=38>