

PVC Vinyl Strip Door Roll 3/50 In. Thickness 6 In. x 3600 In. Clear

MODEL TG-600-ROLL

Loading Dock Equipment / Vinyl Strip Doors



PRODUCT OVERVIEW

Roll vinyl strip door material for replacing damaged strips or adding new strips.

KEY FEATURES

- Vinyl strip design helps to minimize heating and cooling costs
- Clear strips offer visual clarity & employee safety
- Fire resistant vinyl construction is self-extinguishing
- Smooth surface design allows user to comfortably enter & exit

CORE PRODUCT DATA

ASSEMBLED WEIGHT
36 lbs**ASSEMBLED SIZE**
6" W x 0.06" L x 3600" H**SHIP WEIGHT**
56 lbs**PACKAGE 1 SIZE**
18" W x 18" D x 7" H**COLOR / FINISH**
Clear**FREIGHT TYPE**
Parcel**AVAILABILITY** Available**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Opening Width (in.)	6
Opening Height (in.)	3600
Tensile Strength (PSI)	2635
Maximum Tensile Elongation (percent)	388
Graves Tear Load (lb.)	35.4
Graves Tear Extension (in.)	2.07
Load at 100% Elongation (lbs.)	32.2
Strength at 100% Elongation (PSI)	1181
Stiffness in Flexure -23° Celsius (PSI)	1805
Brittleness Temperature by Impact (degrees Cels	35
Recommended Operating Temperature - Range (°C)	-10 to 140
Specific Gravity	1.22
Haze Transmittance (percent)	6.30
Luminous Transmittance (percent)	82.80

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=27>